




Actively Cooled Laser Bar Stack

A-Stack λ 870-890 nm



Features:

Improved cooling efficiency
 No "smile" effect
 Number of bars on demand
 Central wavelength on demand
 Real macro-channels cooling

Suitable for:

Surgical cardiology
 Ophthalmology
 Odontology
 Hair removal

Interstitial laser induced thermotherapy
 Material processing
 Printing

Technical specifications ^(1,2)	
Wavelength ⁽³⁾ [nm]	870 - 890
Wavelength tolerance [nm]	\pm 5
Spectral width, FWHM [nm]	< 5
Wavelength shift [nm/K]	0.33
Output power per laser bar ^(2,4) [W]	CW - up to 100 / QCW - up to 500
Operating current [A]	CW < 120 / QCW < 480
Differential slope, after threshold [W/A]	1.2
Voltage @ connectors ⁽⁵⁾ [V]	2 - 20
Bar to bar pitch [mm]	down to 1.5
Optics (optional)	FAC / SAC / BT
Bars per stack ⁽⁶⁾	1 - 10
Smile [μ m]	< 0.1

- Specifications at 20 °C, at the beginning of the lifetime
- Specifications are subject to chips availability
- Other wavelengths on request
- Expected output power per laser bar can varies based on current and temperature
- Voltage from the power supply must be higher, as due to high current there will be a voltage drop in the cables
- Pitch dependent.

A-STACK / 870- 890 nm
 Version: 1.0.0.0 October 2021
 Product specification are subject to change without notice.
 For complete details, please contact your local MONOCROM sales representative.

MONOCROM S.L.
 C/Vilanoveta 6
 08800 Vilanova i la Geltrú
 Spain

T. +34 938 149 450
 E. sales@monocrom.com
www.monocrom.com

UNE EN ISO 9001:2015